

MC Series



MOD Series
M Series
MC Series
MCS Series
VP Series
100 Series
S Series

- Operating voltage from 10 kVDC to 15 kVDC
- Operating current up to 13 A
- 2 - 5 HV contacts
- For cable sizes AWG 26-14

Housing	
Locking system	threaded coupling
Mounting type (panel mount connector)	4-hole flange
Housing material basis / adapter	brass (CuZn)
Surface plating	nickel (Ni)
Protection class (mated connector)	IP60 (IP65 on request)
Operating temperature	-30°C to +80°C

Contacts 1.6 mm	
Termination method	solder / crimp
Rated current	13 A
Contact resistance	≤ 5 mΩ
Contact diameter	1.6 mm [.063"]
Wire size (AWG / cross section)	AWG 26 - 14 (0.14 mm ² - 2.5 mm ²)
Contact material	brass (CuZn)
Contact plating	silver (Ag) / gold (Au)
Mating cycles	≥ 1,000

Insulation inserts	
Number of contacts	2, 3, 4, 5
Insulation material	PTFE / POM
CTI value	600
Flammability class PTFE	UL94 V-0
Flammability class POM	UL94 HB
Operating temperature PTFE	-50°C to +200°C
Operating temperature POM	-30°C to +120°C
Insulating material group PTFE / POM	I (DIN IEC 60664)

Suitable cable dimensions (single wire)

